


pressure limitation valve


type HPB 65


3-HPB 65

valve type with pilot valve



control valve manuel externally controlled
pressure range PN 0-64 bar
orifice DN 65 mm
connection flange
function manual stepless pressure regulation



 Above stated body materials refer to the valve port connections that get in contact with the media only!


design externally controlled with spring return
body materials ① ④
 ② steel, galvanized ⑤
 ③ ⑥
valve seat metal on metal
seal materials NBR FPM


details needed for main valve

- orifice
- port
- pressure regulating range
- flow rate
- media
- media temperature
- ambient temperature

details needed for pneumatic actuation

- nominal voltage
- type of protection
- actuation pressure range min/max

 The valves' technical design is based on media and application requirements. This can lead to deviations from the general specifications shown on the data sheet with regards to the design, sealing materials and characteristics.

 If order or application specifications are incomplete or imprecise there exists a risk of an incorrect technical design of the valve for the required application. As a consequence, the physical and / or chemical properties of the materials or seals used, may not be suitable for the intended application.

general specifications

ports	HPB	flanges PN 64
function		stepless regulation
pressure regulation range	bar	5-64
Kv value	m ³ /h	max. 60,0
media		liquid - highly viscous - contaminated
abrasive media		
flow direction	P ⇌ R	as marked
operating time	ms	< 400
media temperature	°C	0 to +60
ambient temperature	°C	0 to +50
approvals		
mounting		
weight	kg	42,5
additional equipment		

options

electrical specifications

nominal voltage	U _n	24 V DC	special voltage upon request
	U _n	230 V 50 Hz AC	special voltage upon request
power consumption	DC	4,8 W	2,5 W
	AC	pick up 11,0 VA holding 8,5 VA	
protection	IP 65 (P54)	acc. DIN 40 050	
energized duty rating	ED	100%	
connection		plug acc. DIN EN 175301-803 form B	
additional equipment		illuminated plug with varistor	
optional	M12x1	connector acc. DESINA	connector acc. VDMA
coil		3 positions x 90° / wire diameter 6-8 mm	
max. temperature	media	60°C	
	ambient	50°C	
explosion proof	EEx m II T5	nominal voltage U _n	direct current 24 V 3,25 W
		power consumption	alternating current 230 V 50 Hz 2,90 W

options


pneumatic specifications

actuation pressure range	bar	see actuation pressure-diagram
air consumption		DIN ISO 8573-1 grade of compressed air quality 5/4/3
control		preferably 3/2-way pilot valve during low pressure circulation mode
actuator ports	1	G 1/8


options

■ specifications not highlighted are standard
 ■ specifications highlighted in grey are optional

type HPB 65



actuation pressure-diagram



pressureless circulation mode

